PAINTERS TAPE 006	(24mm/36mm)	Updated Oct'21
TAPE OUS	 creating good paint separation lines. Product Features: Prevents paint from bleeding separation line. 	ing through the tape to create a good paint damage nor leave adhesive residue on the surface up and good tear resistance out the painting project
Product Construction		
Backing	: High-Quality Washi Paper	
Adhesive	: Emulsion Acrylic	
Colour	: Yellow	
Technical Physical Propert	ies	Test Method
Adhesion to Steel	: 1.25 N/cm (11.4 oz/in)	: GB/T 2792-2014
Tensile Strength	: 28 N/cm (16 lbs/in)	: GB/T 30776-2014
Elongation at Break	: 2%	: GB/T 30776-2014
Total Thickness	: 0.095 ± 0.015 mm	
Working Temperature Range	: 0°C to 40°C (32°F to 104°F)	
Note : The above technical infor	mation and data are typical values onl	ly and should not be used for specification purposes
Storage		
Store under normal ambient co	nditions and 50% R.H. in the original ca	arton. To keep away from direct sunlight.
Shelf Life		
This product is guaranteed to b product at room temperature (2		fter delivery, condition to the proper storage of th
Disclaimer		
The technical information and i	ecommendations contained in this do	ocument are based upon tests or experience that w
believe are reliable.		
	-	rformance of the product in a particular application
including the time and environn	nental conditions in which the product	is expected to perform. The user should evaluate an

determine whether the particular product is fit for a particular purpose and is suitable for the user's method of application before use for its intended application. Information is subject to change without notice. Nippon Paint (M) Sdn Bhd will not accept any responsibility or liability whether directly or indirectly for any consequential

loss or damage as a result of our recommendations.