

**ODOURLITE THINNER**
*Updated Apr'23*


Odourlite Thinner can be used to improve paint consistency, it is mainly use in Odourlite Gloss Finish and Odourlite Soft Matt Finish as Thinner.

**Product Features:**

- Low volatility

Paint Type	Product Type	Finishing	Recommended Substrate	Pack Size
Solvent based	Interior & Exterior	Not applicable	Not applicable	5 Litres

**Composition**

Pigment	: Not applicable
Binder	: Not applicable
Thinner	: Mainly Low Aromatic Hydrocarbon

**Technical Data**

Drying Time	: Not applicable
Recoating Time	: Not applicable
Dry Film Thickness	: Not applicable
No. of Coats	: Not applicable
Theoretical Coverage	: Not applicable
Volume Solid	: Not applicable
Flash Point °C	: Not applicable
Shelf Life	: Up to 36 months in tight sealed container

**Application Method**

Brush / Roller	: Not applicable
----------------	------------------

**Recommended Coating System**

Sealer / Primer	: Not applicable
Top Coat	: Not applicable

**Surface Preparation**

Not applicable

**Cleaning**

Clean up equipment immediately after use.

**Safety Precautions**

- Keep container tightly closed and keep out of reach children or away from food and drink.
- Ensure good ventilation during application and drying.
- When using the thinner, it is advisable to wear eye protection.
- In case of contact with eye, rinse with plenty of water immediately and seek medical advice.
- Remove splashes from skin by using soap or water.
- Thinner must always be stored in a cool place.

- When transporting thinner, care must be taken. Always keep container in a secure upright position.
- Dispose off any paint waste in accordance with the appropriate Environment Quality Regulations.

**Note**

\* Theoretical Coverage is based on a mathematical formula

$$\left[ \frac{\text{Volume Solid \%} \times 10}{\text{Dry Film Thickness}} \right] = \text{m}^2/\text{lit}/\text{coat}$$

and does not consider LOSS FACTORS.

Variables like porosity of substrate, application method, dilution ratio, dry film thickness, opacity and so on will affect the loss factor and can vary from 30% - 50% or even more.

The above information is given to the best of our knowledge based on laboratory tests and practical experience.

However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.